

## DECLARATION OF PERFORMANCE

PPF30EN013

1. Unique identification code of the product-type:

***Protex Armeret Dampspærre NG***

2. Intended use:

***Flexible sheets for waterproofing - Plastic and rubber vapour control layers -  
Definitions and characteristics***

3. Producer:

***Juta a.s., Dukelská 417, 544 15 Dvůr Králové nad Labem, Czech Republic  
Tel.: +420 499 209 211, Fax:  
www.juta.cz***

4. Authorised representative:

***not listed***

5. POSV Systems:

***system 3***

6. Harmonised Standard:

***EN 13984:2013***

Identification number of the notified body:

***Institut pro testování a certifikaci a.s., Divize CSI - Centrum stavebního  
inženýrství, Pražská 16, Praha 10 - Hostivař, PSČ 102 00  
Oznámený subjekt 1023***

7. Declared properties:

Essential characteristics	Performance			Harmonised technical specification	
	Units	Nominal value	Tolerance		
Reaction to fire	[class]	E *	-	-	EN 13984:2013
Water tightness	-	conforming	-	-	
Water vapour transmission properties (Sd)	[m]	30	-10	+25	
Determination of resistance to impact	-	npd	-	-	
Joint strength	[N]	npd	-	-	
Maximum tensile force MD/CMD	[N/50mm]	>270 / >200	-	-	
Resistance to tearing MD/CMD	[N]	>140 / >160	-	-	
Resistance to alkali	-	npd	-	-	
Durability of water vapour resistance against ageing	-	conforming	-	-	
Dangerous substances		npd			

Notes: MD - Machine Direction, CMD - Cross Machine Direction, npd - no performance determined; \* - bottomed with insulating compound

8. Relevant technical documentation / specific technical documentation:

***not issued***

9. Properties of the above stated product are in compliance with the set of declared properties. In accordance with Regulation (EU) No. 305/2011, this properties declaration is issued under the sole responsibility of the producer mentioned above.

Signed for and on behalf of the manufacturer by:

Ing. Jiří Hlavatý  
Chairman of the Board

In Dvůr Králové nad Labem, 16.11.2020

